

# The OTTOFLEX system

# More information from specialist suppliers

# The pro's choice for sanitary joints

The OTTOFLEX system consists of

- Primer
- Protective coating
- Slurry Seal Coating
- Sealing Tape
- Wall Sealing Sleeve
- Floor Sealing Sleeve
- Exterior Corners
- Interior Corners



OTTO accessories for the pro

- Cleaner
- Primer
- Back-up foam rods/  
back-filling material
- Hand-operated guns
- Smoothing Agent
- Fugenboy
- Silicone remover

**For renovations:**  
Anti-Mildew-Spray



Supplier's stamp

Index:9999403-GB-07.03.2011  
© Hermann Otto GmbH 2011

**Note:**

The information in the present document corresponds to the status quo on going to print, refer to the index. Owing to the many types and conditions of applications in which our products are used, it is always necessary for the user to test and verify in practice all important product properties for the respective purpose of the applications before using them. To this end, pay attention to the information in the relevant updated technical data-sheet. This information is available on the Internet at [www.otto-chemie.com](http://www.otto-chemie.com). Errors and typographical errors are excepted.

Find out about the other OTTO products for sealing and bonding at [www.otto-chemie.com](http://www.otto-chemie.com)



**Sealants • Adhesives**

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY

Tel.: +49-(0)8684-908-0 · Fax: +49-(0)8684-908-539

E-mail: [info@otto-chemie.de](mailto:info@otto-chemie.de) · Internet: [www.otto-chemie.com](http://www.otto-chemie.com)



**The premium  
sanitary silicone  
with unequalled  
finishing properties  
in 75 colours**



**Sealants • Adhesives**

# Waterproof joints for over 30 years

# The most important features at a glance

## OTTOSEAL® S 100

For decades OTTO's most successful product for professional sanitary joints has guaranteed fast and smooth joints in millions of baths, kitchens, entrance halls and toilets.

Its **excellent smoothability**, it not being very stringy and the unequalled multitude of colours make OTTOSEAL® S 100 the market leader in its field.

Our advice: mask off tiles before applying primer and/or sealant



clean



if necessary use primer



place foam backrod



fill joint



wet Fugenboy with Smoothing agent then smooth off



### Properties

- Acetoxy curing RTV-1 silicone sealant
- Unique processing characteristics
- Excellent adhesion on ceramic surfaces
- All colours contain fungicides
- Available in 75 colours ex warehouse
- UV-resistant
- Excellent weathering and ageing resistance

### Applications

- Sealing of connecting joints in the entire bathroom area, between tiles and bath tubs, shower basins, wash basins and shower partition walls
- Sealing of expansion joints in floor and wall areas

### Standards and tests

- For use in low emission buildings in compliance with TOXPROOF - TÜV Rheinland Produkt und Umwelt GmbH (product and environment).

### Notice

Before applying the adhesive / sealant the user has to ensure that it is compatible with the surrounding building materials (solid, liquid and gaseous) and will not be damaged or altered by them (e.g. discoloured). As for the building materials that will be used at a later stage in the surrounding area of the adhesive / sealant the user has to clarify beforehand that the substances or their evaporations do not lead to an impairment or alteration (e.g. discolouration) of the adhesive / sealant. If in any doubt the user has to consult the manufacturer of the building material concerned.