



Xi



Safety Data Sheet

ULTRAPLAN RENOVATION

Safety Data Sheet dated 13/5/2010, version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade name: ULTRAPLAN RENOVATION

Product type and use: Cement based levelling mortar.

Supplier:

MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

Emergency telephone number of the company and/or of an authorised advisory centre:

MAPEI U.K. Ltd - phone: +44-121-5086970

fax: +44-121-5086960

www.mapei.co.uk

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

2. HAZARDS IDENTIFICATION

Properties / Symbols:

Xi Irritant

R Phrases:

R43 May cause sensitization by skin contact.

If brought into contact with the skin, the product may cause sensitisation of the skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components within the meaning of EEC directive 67/548 and corresponding classification:

40% - 50% free crystalline silica ($\text{Ø} > 10 \mu$)

CAS: 14808-60-7 EC: 238-878-4

substance with a Community workplace exposure limit

2.5% - 5% Portland cement, Cr(VI) < 2 ppm

CAS: 65997-15-1

Xi; R38-41-43

4. FIRST AID MEASURES

Contact with skin:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Contact with eyes:

Wash immediately and thoroughly with running water, keeping eyelids raised, for at least 10 minutes. Following this, protect the eyes with sterile gauze or a clean, dry, handkerchief. OBTAIN A MEDICAL EXAMINATION.

Swallowing:

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

Inhalation:

Ventilate the premises. The patient is to be removed immediately from the premises contaminated and made to rest in a well ventilated area. Should the patient feel unwell, consult a physician.

Safety Data Sheet

ULTRAPLAN RENOVATION

5. FIRE-FIGHTING MEASURES

The product does not present a fire hazard
Extinguishers not to be used:
None in particular.

6. ACCIDENTAL RELEASE MEASURES

Measures for personal safety:
None in particular
Environmental measures:
Cleaning methods:
Rapidly recover the product, wearing protective clothing.
Scoop into containers and seal for disposal.
After the product has been recovered, rinse the area and materials involved with water.

7. HANDLING AND STORAGE

Handling precautions:
Avoid contact with skin and eyes and exposure to high dust concentration.
Avoid powder development and deposit
Incompatible materials:
Keep away from water or from damp surroundings.
Storage conditions:
Always keep the containers tightly closed.
Instructions as regards storage premises:
Adequately ventilated premises.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values(TLV-TWA): (powder)10 mg/m³
Precautionary measures:
Give adequate ventilation to the premises where the product is stored and/or handled.
Respiratory protection:
Not needed for normal use.
Use adequate protective respiratory equipment, when above TLV.
A dust mask should be worn if above exposure limits.
Protection for hands:
Use protective rubber gloves.
Neoprene gloves are suggested (0,5 mm) not recommended gloves: none
Eye protection:
Safety goggles.
Protection for skin:
Use clothing that provides comprehensive protection to the skin.
Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Exposure limit value of single components:
free crystalline silica ($\varnothing > 10 \mu$)
TLV TWA:: 0,05 mg/m³ (respirable fraction)
Portland cement, Cr(VI) < 2 ppm
TLV TWA:: (polvere)10 mg/m³

Carry out the control of the concentrations of the substances with exposure limits assigned, in the working place according to local dispositions

9. PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet

ULTRAPLAN RENOVATION

Appearance:	powder
Colour:	grey
Odour:	slight, typical of cement
pH:	N.A.
pH(water dispersion, 10%):	12
Melting point:	N.A.
Boiling point:	== °C
Flash point:	== °C
Solid/gas flammability:	N.A.
Autoignition temperature:	== °C
Explosion limits(by volume):	==
Oxidizing properties:	N.A.
Vapour pressure:	N.A.
Relative density:	1.1 g/cm ³ (23°C)
Solubility in water:	partly soluble
Lipid solubility:	insoluble
Viscosity:	N.A.
Vapour density (air=1):	N.A.

10. STABILITY AND REACTIVITY

Conditions to avoid:
Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

Route(s) of entry:

Ingestion:	Yes
Inhalation:	Yes
Contact:	No

Toxicological information related to the product:

No toxicological data are available at the moment on the product itself.

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

The product does not contain toxicologically relevant substances.

Corrosive/Irritating Properties:

Skin:
The product can cause irritation by contact.

Eye:
The product can cause irritation by contact

Sensitizing Properties:

Frequent and prolonged skin contacts with cement paste may cause dermatitis.

Carcinogenic Effects:

No effects are known.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

Additional Information:

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Safety Data Sheet

ULTRAPLAN RENOVATION

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

12. ECOLOGICAL INFORMATION+

Biodegradability: no data available on the preparation.

Adopt good industrial practices, so that the product is not released into the environment.

13. DISPOSAL CONSIDERATIONS

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Where applicable, refer to the following regulatory provisions : 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of hardened product (EC waste code) : 17 01 01

Disposal of not hardened product (EC waste code) : 17 01 01

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

14. TRANSPORT INFORMATION

UN Number:	==
Rail/Road(RID/ADR):	no dangerous good
Sea (IMO/IMDG):	no dangerous good
MAR/POL 73/78,Annex III:	No
Air (ICAO/IATA):	no dangerous good

15. REGULATORY INFORMATION

Council Directive 67/548/EEC (Classification, packaging and labelling of dangerous substances) and subsequent amendments. Commission Directive 1999/45/EC (Classification, packaging and labelling of dangerous preparation) and subsequent amendments. Commission Directive 98/24/EC (Protection of the health and safety of workers from the risk related to chemical agent). Commission Directive 2000/39/EC (Occupational exposure limit values). Regulation (EC) No 1907/2006 (REACH).

Symbols:

Xi Irritant

R Phrases:

R43 May cause sensitization by skin contact.

S Phrases:

S22 Do not breathe dust.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

Contents:

Portland cement, Cr(VI) < 2 ppm

16. OTHER INFORMATION

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

ACGIH - Threshold Limit Values - 2004 edition

SAX'S - Dangerous properties of industrial materials

Safety Data Sheet

ULTRAPLAN RENOVATION

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Text of phrases referred to under heading 3:

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitization by skin contact.