

**GEOCHEM**



PROFESSIONAL  
BUILDING  
CHEMICAL  
RANGE

# ACRYLIC ROOFING COMPOUND

## SINGLE APPLICATION, HIGH PERFORMANCE, WATERPROOFING ROOFING PROTECTION COMPOUND

**Geochem Acrylic Roofing Compound** is a single application, high performance, waterproofing roofing protection compound with synthetic fibre reinforcement. It is ideal for immediate emergency repair and the general maintenance of most conventional types of roof and can be applied in wet conditions, providing a tough flexible seamless coating with excellent crack-bridging properties.

**Geochem Acrylic Roofing Compound** can be used on concrete, fibre/cement, roofing felt, mastic, asphalt, existing bituminous roof coatings, guttering (plastic and metal), downpipes, gulleys, flashings, vents, lead work, rigid PVC, corrugated iron, metals, slates, brickwork, tiles, lead, copper and zinc.

### **Geochem Acrylic Roofing Compound:**

- Instant waterproof protection – Fibre reinforced.
- Can be used in the wet and on wet surfaces
- One coat application – Easy to apply & ready to use (no need to mix)
- For all roofs, gutters and gulleys
- Outstanding adhesion



## TECHNICAL DATA

<b>Form</b>	Grey brushable liquid
<b>Storage Life</b>	12 Months stored between 5°C and 25°C in original containers

Specification writers: These values are not intended for use in preparing specifications. Please contact your local **Geocel® Sales Representative** prior to writing specifications on this product.

## SURFACE PREPARATION

Before applying, ensure surfaces are clean, structurally sound and free from dust, stone chippings, lichen, moss and standing water or any contaminants. Repair all splits, cracks and grazed areas where necessary.

Fill holes and imperfections with **Geocem Bitumen Mastic**. Stick down loose felt etc with **Geocem Felt Adhesive**. Blisters in felt must be cut, dried, re-bonded and sealed.

## APPLICATION

Stir well before use. Apply by brush in one coat at a rate of 1-2 kilo per m<sup>2</sup> ensuring an even coverage free from pinholes. **Geocem Acrylic Roofing Compound** will fill and bridge cracks up to 10mm wide, but where wider cracks are present, these should be covered with a suitable flexible scrim bedded into the coating.

On damp surfaces **Geocem Acrylic Roofing Compound** should first be worked into the surface with a brush or roller to disperse excess moisture and ensure a good bond. Immediately afterwards, further material should then be brushed onto the surface.

In extreme cases a second coat may be applied 2-3 days after initial application.

## COVERAGE

Approximately 1-2 kilo per m<sup>2</sup> per coat when applied as directed.

## CLEANING

All tools should be cleaned immediately after application with brush cleaner or white spirits.

## PACKAGING

**Geocem Acrylic Roofing Compound** is available in grey 5kg and 20kg tins.

## LIMITATIONS

Do not apply to roof lights, windows, glass or translucent sheets, as these will constitute a hidden hazard.

## HEALTH AND SAFETY

**Geocem Acrylic Roofing Compound** is a solvent based product and gives off inflammable vapours. Appropriate protective equipment should be worn to avoid skin and eye contact and breathing fumes. Keep away from naked flames. Do not smoke. For further information please refer to Health and Safety data sheets available on request.

## TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel® Technical Service**.

**IMPORTANT NOTE** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damages.

# Geocel®

Geocel Limited

Western Wood Way, Langage Science Park, Plympton, Plymouth, Devon, PL7 5BG

Tel: 01752 334350 Fax: 01752 202065 Email: [info@geocel.co.uk](mailto:info@geocel.co.uk)

[www.geocel.co.uk](http://www.geocel.co.uk)