

# Geocel® ECOCHEM SOLVENT FREE WATER SEAL

**Geocel® Ecochem Solvent Free Water Seal** not only waterproofs, but protects brickwork against rain, damp and frost damage. It is fast acting and lasts, is easy to apply and prevents water penetration while allowing trapped moisture to escape.

**Geocel® Ecochem Solvent Free Water Seal** protects brickwork, pointing, concrete, stonework and grouting.



Water beading on bricks after treatment with **Geocel® Ecochem Solvent Free Water Seal**.

#### **Geocel® Ecochem Solvent Free Water Seal:**

- Contains no harmful solvents
- Outperforms solvent based products
- Only one coat required
- Fast acting
- Easy to apply by spray or brush
- Protects brickwork, pointing, concrete, stonework and grouting



## TECHNICAL DATA

|                        |  |
|------------------------|--|
| <b>Form</b>            | Liquid   |
| <b>Storage Life</b>    | 12 Months stored between 5°C and 25°C in original containers |
| <b>Water Bead Time</b> | 2 hours at 23°C 50% RH                                       |

Specification writers: These values are not intended for use in preparing specifications. Please contact your local **Geocel® Sales Representative** prior to writing specifications on this product.

## SURFACE PREPARATION

Clean the surfaces to be treated; removing any dirt, grease, mould or fungal growth and any loose surface coatings. To avoid residue splashes on wood, metal, window or door frames and glass, these surfaces should be covered prior to using **Geocel® Ecochem Solvent Free Water Seal**. Plants should be protected with plastic sheets.

## APPLICATION

Shake well before use. **Geocel® Ecochem Solvent Free Water Seal** must be applied undiluted on a dry surface. Moving from top to bottom apply with a brush or using low pressure spraying (avoid using a very fine mist). Apply using an even coat, spread well, and brush out runs and uneven patches immediately. Do not allow any runs to dry into surface. Finish a given area without stopping.

## COVERAGE

5 Litres will treat approximately 50m<sup>2</sup>.

## CLEANING

Immediately clean up and thoroughly rinse any spills or misapplied product. Remove any splatters on glass with a household cleaner. Clean equipment with water.

## PACKAGING

**Geocel® Ecochem Solvent Free Water Seal** is available in 5 litre containers packed in boxes of 2

## LIMITATIONS

Do not apply when temperature is at or below 5°C or if rain is imminent prior to the treated area drying. Not suitable for flooring or paving applications and overpainting is not recommended. May cause slight darkening of natural stone surfaces, if in doubt undertake a trial application in an inconspicuous area.

## HEALTH AND SAFETY

Health and Safety data sheets available on request. EU limit value for this product (Cat C/c) 75g/L (2007) 40g/L (2010). This product contains maximum 2g/L VOC.

## TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel® Technical Service**.

**IMPORTANT NOTE** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damages.

# Geocel®

Geocel Limited

Western Wood Way, Langage Science Park, Plympton, Plymouth, Devon, PL7 5BG

Tel: 01752 334350 Fax: 01752 202065 Email: [info@geocel.co.uk](mailto:info@geocel.co.uk)

[www.geocel.co.uk](http://www.geocel.co.uk)