

**GEOCHEM**



PROFESSIONAL  
BUILDING  
CHEMICAL  
RANGE

# LIQUID CEMENT COLOUR

## PERMANENT CEMENT COLOUR

**Geochem Liquid Cement Colour** is a high quality pigment dispersion which produces a permanent colour in concrete, mortars, floors and renders for bricklaying or pointing and roof tiling to verges and ridges. It is also ideal for paths, paved areas, fence posts, garden ornaments, etc. The liquid disperses easily into the mix to give a uniform shade for each mix batch.

### **Geochem Liquid Cement Colour**

- Permanent cement colour for use in concrete, mortar, render and screeds.
- Easy to use – Disperses quickly and evenly throughout the mix.
- Suitable for internal and external use.
- Strong colours to minimise addition rate.



## TECHNICAL DATA

<b>Form</b>	Liquid
<b>Storage Life</b>	12 Months unopened stored between 5°C and 25°C in original containers
<b>Dosage</b>	up to 5% on cement content by weight

Specification writers: These values are not intended for use in preparing specifications. Please contact your local **Geocel® Sales Representative** prior to writing specifications on this product.

## APPLICATION

Always shake container before use as product can settle.

Liquid colour can be added to the dry mix or gauging water at the addition rate of up to 1.25 litres per 25kg of cement in the mix.

Variations of shade are dependant on usage i.e. types of aggregates and cement used. Trial batches should be carried out to obtain shade required.

## PACKAGING

**Geocem Liquid Cement Colour** is available in 1 Litre in boxes of 12 and 5 Litre in boxes of 2.

**Geocem Liquid Cement Colour** is available in black and red.

## LIMITATIONS

**Geocem Liquid Cement Colour** can not be used as a surface stain and must always be incorporated into the cement based mix.

## HEALTH AND SAFETY

**Geocem Liquid Cement Colour** is not classified as hazardous, but prolonged contact may cause irritation. Please refer to Health and Safety data sheets available on request.

## TECHNICAL SERVICE

For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact **Geocel® Technical Service**.

**IMPORTANT NOTE** The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Geocel's products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Geocel's sole warranty is that the product will meet the Geocel sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

Geocel specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability.

Geocel disclaims liability for any incidental or consequential damages.

# Geocel®

Geocel Limited

Western Wood Way, Langage Science Park, Plympton, Plymouth, Devon, PL7 5BG

Tel: 01752 334350 Fax: 01752 202065 Email: [info@geocel.co.uk](mailto:info@geocel.co.uk)

[www.geocel.co.uk](http://www.geocel.co.uk)